AKTIV BD7719 (Blocked Catalyst)

AKTIV BD7719 is an polymeric blocked DNNSA catalyst which utilizes high temperature applications.

CHEMICAL COMPOSITION I

Polymeric locked Dinonylnaphthalene sulfonic acid

TYPICAL PROPERTIES

- Appearance	: Clear, dark brown liquid
- Active(%)	: 30
- Specific Gravity	: 0.94 ± 0.03 g/L
- Gardner	: N/A
- Volatile	: Xylene/MIBK
- Recommended curing range	: 150 ~ 200℃(300 ~ 400 °F)

ADVANTAGES I

- 1. High temperature application
- 2. Excellent solubility in aromatic and aliphatic hydrocarbons
- SOLUBILITY I

Excellent soluble in aromatic and aliphatic hydrocarbones. soluble alcohols, glycol ethers, glycols and ketones. Insoluble in water.

APPLICATION I

- 1. Coil Coatings
- 2. Can Coatings
- 3. Appliance finishes
- 4. General industries
- 5. Electrostatic spraying

HANDLING

BD7719 is classified as a flammable liquid. Storage under excessive heat conditions should be avoided. safe handling of this product should include the use of safely glasses and gloves. Avoid breathing vapors - use with adequate ventilation.

PACKING UNIT 180 Kgs PVC D/M