

AKTIV BD7733

(Blocked Catalyst)

AKTIV BD7733 is a Polymeric blocked DDBSA catalyst

■ CHEMICAL COMPOSITION ■

Polymeric blocked Dodecylbenzene sulfonic acid

■ TYPICAL PROPERTIES ■

- Appearance	: Clear, dark brown liquid
- Active(%)	: 25
- pH	: N/A
- Specific Gravity	: 1.0 ± 0.03 g/L
- Gardner	: 4 max.
- Volatile	: Xylene
- Recommended curing range	: 120 ~ 180°C(250 ~ 360°F)

■ ADVANTAGES ■

1. Excellent electrostatic spray(non-aqueous)
2. Good intercoat adhesion

■ SOLUBILITY ■

Soluble in aliphatic & aromatic hydrocarbons. Partially soluble in alcohols, glycol ethers, glycols and esters. Insoluble in water

■ APPLICATION ■

1. Coil Coatings
2. Automotive Topcoats
3. Electrostatic spray coatings
4. General industries

■ HANDLING ■

BD7733 is classified as a flammable liquid. Storage under excessive heat conditions should be avoided. safe handling of this product should include the use of safety glasses and gloves.

Avoid breathing vapors - use with adequate ventilation.

■ PACKING UNIT ■

180 Kgs PVC D/M