# **ILDISPER DS-100**

## (Dispersant for PVC-Plastisol)

ILDISPER DS 100, newly developed has excellent dispersing effect on handling PVC-Plastisol. And CaCO3, TiO2 and ZnO are also available to use.

SPECIFICATIONS

- Appearance : Clear, slightly yellowish liquid
- Viscosity(mPa.s) :700 (B type. 25°C)
- Specific gravity : 1.03 (25°C)

### FEATURES

- 1. Good stability for acid and alkali area.
- 2. Good ability for wetting and dispersing.
- 3. It helps you get more uniform sized solid.
- 4. If you use it with depressant agent, you can increase pigment more than 50%. So, cost saving and changing of physical properties are possible.

#### APPLICATION I

• We suggest you use this product with the dosabe 0.5 ~ 3.0%

Titanium Dioxide	: 1 ~ 3%
Calcium Carbonate	: 1 ~ 2%
Zinc Oxide	: 1 ~ 2%

### ■ HANDLING PRECAUTIONS ■

- Wear protective eyeglasses, protective glove, or goggles on handling.
- In case of contacts with skin, wash thoroughly with soap.
- In case of contacts with eye, wash thoroughly with plenty of water immediately and get medical aid.
- In case of ingestion, get medical aid as soon as possible.
- Wash your hands with soap thoroughly and gargle after handling.
- Keep away from fire, heat or any other possible source of ignition on handling and storage.
- Store 50 ~ 40°C and Keep away from freezing to maintain high efficiency.

Additional handling information is contained in the material safety data sheet which is available on request.

PACKING UNIT

200kg Drum