

ILTOL SPW30(AC)

(Oil removing agent)

ILTOL SPW30(AC) is a anionic and nonionic type oil removing agent.

ILTOL SPW30(AC) has high oil removing properties for machine oil & silicone oil(spandex), contaminated dirt on transport and various impurities. Because has excellent dispersion & emulsion properties, prevent for reattachment.

■ SPECIFICATIONS ■

Appearance	: Colorless transparent liquid
Chemical component	: Anionic / Nonionic surfactant blend
Solubility	: Easily soluble in cold water
Ionic	: anionic / nonionic
Active contents (%)	: 35
PH (1% aq. Soln.)	: 4 -5

■ FEATURES ■

1. Because non solvent type, produce no side effects.
2. If use with alkali or acids, show excellent oil removing effects more than an unused.
3. Because has excellent dispersion & emulsion properties for machine oil & spindle oil, & spandex oil prevent for reattachment.
4. Excellent wax(used twisted thread) emulsifying properties.
5. Easily soluble in cold water.

■ APPLICATION ■

According to contaminated degree, the require amount is differnt, but generally 1 ~ 2 g/L are recommended.

Especially, If use with soda ash 2 g/L, show excellent oil removing effects more than an unused.

SPANDEX oil removing process :

Acetic Acid 2g/l, ILTOL SPW30(AC), 2g/l Temp 70℃ - 80℃ 45min.

■ PACKING UNITS ■

Net 100Kgs or 200 Kgs PVC D/M